

# BallStar™ Tip Screwdrivers

## - ProGuard™ Finish -

- Fits all TORX® and Star screws
- Ball End inserts into a screw at a 20° angle
- Ball End saves time by quickly funneling tool into screw
- Superior Ball End strength and working angle
- Works in hard to reach places



ProGuard™ finish delivers superior corrosion protection



Handles are color coded for easy recognition

Green=TORX®



BallStar™ Tips

| Sets              | PART# | MODEL# | PCS | CONTENTS                              | QTY | LIST |
|-------------------|-------|--------|-----|---------------------------------------|-----|------|
| <b>BALL STAR™</b> | 13546 | STX6   | 6   | T6, T7, T8, T9, T10, T15              | 1   |      |
|                   | 13532 | STX8   | 8   | T9, T10, T15, T20, T25, T27, T30, T40 | 1   |      |

SINGLE PACKAGING



| Singles           | SIZE | INCH | MM  | INCH | MM  | PART# | QTY | LIST EA |
|-------------------|------|------|-----|------|-----|-------|-----|---------|
| <b>BALL STAR™</b> | T6   | 2.6  | 65  | 4.7  | 119 | 12706 | 2   |         |
|                   | T7   | 2.6  | 65  | 4.7  | 119 | 12707 | 2   |         |
|                   | T8   | 2.6  | 65  | 5.0  | 126 | 12708 | 2   |         |
|                   | T9   | 2.6  | 65  | 5.0  | 126 | 12709 | 2   |         |
|                   | T10  | 2.8  | 70  | 5.2  | 132 | 12710 | 2   |         |
|                   | T15  | 2.9  | 73  | 6.4  | 161 | 12715 | 2   |         |
|                   | T20  | 3.2  | 81  | 7.5  | 191 | 12720 | 2   |         |
|                   | T25  | 3.4  | 87  | 7.7  | 197 | 12725 | 2   |         |
|                   | T27  | 3.8  | 97  | 8.7  | 220 | 12727 | 2   |         |
|                   | T30  | 4.2  | 106 | 9.0  | 229 | 12730 | 2   |         |
|                   | T40  | 4.6  | 117 | 9.4  | 240 | 12740 | 2   |         |
|                   | T45  | 5.2  | 132 | 10.0 | 255 | 12745 | 1   |         |
|                   | T50  | 6.0  | 153 | 10.9 | 276 | 12750 | 1   |         |
|                   | T55  | 6.8  | 172 | 11.6 | 295 | 12755 | 1   |         |

*Did you know...?*

BallStar™ tools work at a 20° angle; screws can be turned continuously without constantly taking the tool out of the screw, repositioning it and reinserting it, even at angles up to 20°.

# Tamper Resistant TORX® Screwdrivers

## - ProGuard™ Finish -

- Fits all TORX® and Star tamper resistant screws
- Burr free tool tips help tools seat fully in screw head
- Precision machined tips transfer more torque to the screw and reduces stripping

ProGuard™ finish delivers superior corrosion protection



Handles are color coded for easy recognition

Green=TORX®



Tamper Resistant TORX® Tips

| Sets         | PART# | MODEL#  | PCS | CONTENTS                                      | QTY | LIST |
|--------------|-------|---------|-----|---|-----|------|
| <b>TORX®</b> | 33831 | TR-SX7S | 7   | TR7, TR8, TR9, TR10, TR15, TR20, TR25         | 1   |      |
|              | 33834 | TR-SX8  | 8   | TR9, TR10, TR15, TR20, TR25, TR27, TR30, TR40 | 1   |      |

SINGLE PACKAGING



| Singles      | SIZE | INCH | MM  | INCH | MM  | PART# | QTY | LIST EA |
|--------------|------|------|-----|------|-----|-------|-----|---------|
| <b>TORX®</b> | TR7  | 4.5  | 114 | 6.7  | 169 | 33807 | 1   |         |
|              | TR8  | 4.8  | 121 | 7.2  | 182 | 33808 | 1   |         |
|              | TR9  | 4.9  | 124 | 7.3  | 186 | 33809 | 1   |         |
|              | TR10 | 5.0  | 128 | 7.4  | 189 | 33810 | 1   |         |
|              | TR15 | 5.1  | 131 | 8.6  | 219 | 33815 | 1   |         |
|              | TR20 | 5.4  | 138 | 9.8  | 248 | 33820 | 1   |         |
|              | TR25 | 5.7  | 144 | 10.0 | 253 | 33825 | 1   |         |
|              | TR27 | 5.8  | 147 | 10.6 | 270 | 33827 | 1   |         |
|              | TR30 | 6.0  | 153 | 10.9 | 276 | 33830 | 1   |         |
|              | TR40 | 6.3  | 159 | 11.1 | 282 | 33840 | 1   |         |

*Did you know...?*

Bondhus' ergonomic handle design greatly reduces fatigue associated with repetitive tasks and the application of torque.

