



[Americas PDS Database](#) > [Sta-Lube Nickel Anti-Seize Lubricating Compound](#)

---



# Sta-Lube Nickel Anti-Seize Lubricating Compound

## ATTRIBUTES –

---

### Item Number

1007946

### Legacy Number

SL35911

### Product Description

Sta-Lube Nickel Anti-Seize is a nickel based formula that is free of copper, lead, sulfides and chlorides. This premium quality lubricant has excellent high temperature and chemical resistance. Conductive.

### Applications

Catalyst beds, reaction chambers, special alloy fittings. May be used on fittings, bushings, flanges, headers, nuts, screws, studs, threaded surfaces, pipes, plugs, and manifolds to prevent seizing and galling of surfaces.

**Unit Package Description**

8 Ounce Brush-Top Bottle

**Brand**

CRC

**Net Fill**

8 Wt Oz

**UPC Code**

072213359114

**Unit Dimensions**

4.25H x 2.5W x 2.5D in

**Units Per Case**

12

**Case Dimensions**

5H x 10.0W x 6.63D in

**Cases per pallet USA**

108

**Appearance**

Silver Paste

**Flash point (F)**

425°F

**Flash point (C)**

218°C

**Flammability Class - CPSC**

Not a Consumer Product

**Spec Gravity Concentrate**

1.18

**KB Value**

N/A

**Plastic Safe**

Yes

**Film Type**

Wet

**Evaporation Rate**

Not Applicable

**Dielectric Strength**

Not Determined

**Timken Ok Load (lbs)**

N/A

**Propellant**

None

**Military Specification Number**

Mil-PRF-907E

**DOT Proper Shipping Name**

Not Regulated

**4 Ball EP**

Not Determined

**4 Ball Wear**

Not Determined

**Drop Point**

None

**pH**

Neutral

**ISO Viscosity Grade**

Not Applicable

**NLGI Grade**

1

**SAE Grade**

N/A

**Water Washout**

Not Determined

**Working Temp (F)**

-95 to 2600°F

**Working Temp (C)**

-70.6 to 1427°C

**VOC % (Consumer Product def)**

1.8

**VOC g/L (Consumer Product def)**

21.2

**VOC lbs/gal (Consumer Prod def)**

0.18

**VOC Category**

Anti-Seize Lubricant - Non-Aerosol

**Removal (How To)**

Remove with general purpose degreaser.