

120XP™ ELECTRONIC FLEX HEAD TORQUE WRENCHES

Torque Accuracy of +/- 2% Clockwise
Delivers high performance

120XP™ Head
Provides a 3° ratcheting arc

Target Torque Alert
Vibrating handle, buzzer, and LCD screen alerts when target torque is reached

3 Function Modes and 5 Measurement Units
For additional versatility

Flexible Ratcheting Head
Flexes up to 15° for improved access

10 Available Preset Torque Settings
To quickly access frequently repeated applications

Knurled Aluminum Handle
With clearly marked midpoint

120 POSITION
3° SWING ARC™

+/- 2%
ACCURACY™

FLEX HEAD DESIGN™

MULTI-NOTIFICATION™

Cat. No.	Drive Size	Primary Scale Range	Primary Scale Increments	Alt. Scale Range	Alt. Scale Increments	Tooth Count	Head Thickness	Head Width	Overall Length	Product Weight
85194	1/4"	2 - 20 ft-lbs	0.1 ft-lbs	2.7 - 27 Nm	0.1 Nm	120	0.4"	1.0"	15.5"	1.6 lbs
85195	3/8"	10 - 100 ft-lbs	0.1 ft-lbs	13.5 - 135 Nm	0.1 Nm	120	0.6"	1.3"	15.9"	1.9 lbs
85196	1/2"	25 - 250 ft-lbs	0.1 ft-lbs	34 - 340 Nm	0.1 Nm	120	0.7"	1.8"	24.3"	3.0 lbs

MICROMETER TORQUE WRENCHES

Torque Accuracy of +/- 3% Clockwise
Delivers high performance

Thin Profile, Sealed Tear-Drop Head
For access and durability

High Definition Scale Markings
Highly visible and easy to read

Flexible Ratcheting Head
Flexes up to 30° for improved access

Pull Adjustment Collar
For quick and easy torque setting changes

Knurled Aluminum Handle
With clearly marked midpoint

+/- 3%
ACCURACY™

LOW PROFILE HEAD™

FLEX HEAD DESIGN™

Cat. No.	Certified Model No.	Drive Size	Head Style	Primary Scale Range	Primary Scale Increments	Alt. Scale Range	Alt. Scale Increments	Tooth Count	Head Thickness	Head Width	Overall Length	Product Weight
85060M	85060MCERT	1/4"	Standard	30 - 200 in-lbs	1 in-lbs	4 - 23 Nm	0.1 Nm	22	0.5"	1.1"	10.5"	1.8 lbs
85061M	85061MCERT	3/8"	Standard	20 - 250 in-lbs	1 in-lbs	5 - 29 Nm	0.2 Nm	30	0.7"	1.4"	14.0"	2.0 lbs
85062M	85062MCERT	3/8"	Standard	10 - 100 ft-lbs	1 ft-lbs	20 - 142 Nm	1.0 Nm	30	0.7"	1.4"	18.0"	2.5 lbs
85063M	85063MCERT	1/2"	Standard	20 - 150 ft-lbs	1 ft-lbs	34 - 210 Nm	1.0 Nm	32	0.8"	1.75"	21.9"	3.1 lbs
85066M	85066MCERT	1/2"	Standard	30 - 250 ft-lbs	2 ft-lbs	54 - 353 Nm	3.0 Nm	32	0.8"	1.75"	24.3"	3.5 lbs
85086M	85086MCERT	3/8"	Flex	5 - 75 ft-lbs	0.5 ft-lbs	10 - 105 Nm	1.0 Nm	30	0.7"	1.4"	17.7"	2.4 lbs
85087M	85087MCERT	1/2"	Flex	30 - 250 ft-lbs	2 ft-lbs	54 - 353 Nm	3.0 Nm	36	0.9"	1.75"	25.3"	3.8 lbs
85065M	85065MCERT	3/4"	Standard	100 - 600 ft-lbs	2.5 ft-lbs	153 - 831 Nm	4.0 Nm	36	1.1"	2.6"	42.4"	15.8 lbs
85067		1"	Standard	150 - 750 ft-lbs	5 ft-lbs	237 - 983 Nm	5.0 Nm	24	1.3"	2.8"	48.8"	14.1 lbs
85068		1"	Standard	200 - 1000 ft-lbs	5 ft-lbs	305 - 1322 Nm	5.0 Nm	24	1.3"	2.8"	73.0"	23.3 lbs