

Tough gets the job done.  
Smart gets the job done right.

## PRO SERIES NY-CLAD® STEEL TAPES

- Fast 3-to-1 blade retraction saves time in the field
- Durable nylon coating on blade resists wear under extreme conditions
- Steel blade will not stretch under normal use



| Cat. No. | Case Color | Blade Width | Blade Length | Blade Style | Product Weight |
|----------|------------|-------------|--------------|-------------|----------------|
| PS1806N  | Orange     | 1/2 in      | 100 ft       | E4          | 2.02 lb        |
| PS1806DN | Orange     | 1/2 in      | 100 ft       | E5          | 1.98 lb        |
| PS1808N  | Orange     | 1/2 in      | 200 ft       | E4          | 3.04 lb        |
| PS1808DN | Orange     | 1/2 in      | 200 ft       | E5          | 3.14 lb        |
| PS1809DN | Orange     | 1/2 in      | 300 ft       | E5          | 4.11 lb        |

## 3-TO-1 REWIND OPEN REEL FIBERGLASS TAPE MEASURE

- Open frame design helps reduce weight and protects blade for durability
- Positioning spike is designed to show measurement starting points
- End-hook teeth bite into wood to resist loosening
- Great for measuring distances and lengths up to 100 ft.
- Compact rewind handle is designed to not hit your knuckles
- Large handle opening allows for easy work with gloves



| Cat. No. | Blade Width | Blade Length | Blade Style |
|----------|-------------|--------------|-------------|
| L1706N   | 1/2 in      | 100 ft       | C11         |


## CLOSED REEL FIBERGLASS TAPE MEASURES

- Lightweight high impact ABS winding drum for smooth tape recovery
- Non-conductive easy-to-read black and red markings on a yellow background
- Durable 1/2"-wide fiberglass tape with protective coating



| Cat. No. | Case Color | Blade Width | Blade Length | Blade Style | Product Weight |
|----------|------------|-------------|--------------|-------------|----------------|
| T703     | Rawhide    | 1/2 in      | 50 ft        | C1          | 0.90 lb        |
| 703D     | Rawhide    | 1/2 in      | 50 ft        | C2          | 0.80 lb        |
| 706L     | Rawhide    | 1/2 in      | 100 ft       | C1          | 1.20 lb        |
| 706D     | Rawhide    | 1/2 in      | 100 ft       | C2          | 1.30 lb        |

LONG TAPES



## D3 CHROME CLAD® & NUBIAN®

- 1/2"/13mm width only
- Markings both sides
- Graduated in millimeters on one side; other side instantaneous feet and inches to 1/8ths



## D5 NUBIAN®

- 1/2" width only
- Nubian® blade
- Markings one side only
- Graduated feet and inches to 1/8ths; instantaneous foot readings



## D7 NUBIAN®

- 1/2" width only
- Nubian® blade
- Graduated in meters; numbered in millimeters



## E2 CHROME CLAD®

- 1/4"/6mm width only
- Chrome Clad® blade
- Markings on both sides
- Graduated millimeters one side
- Graduated feet, inches and 1/8ths other side




## E4 NY-CLAD® YELLOW

- 1/2" width only
- Nylon-clad yellow blade
- Black and red markings one side only
- Graduated feet and inches to 1/8ths with instantaneous readings
- Numbered with feet and instantaneous foot markings in red and inches in black



## D4 CHROME CLAD® & STAINLESS STEEL

- 1/2" width only
- Markings one side only
- Graduated feet and inches to 1/8ths; instantaneous foot readings



## D6 CHROME CLAD®

- 1/2"/13mm width
- Chrome Clad® blade
- Black and red markings on metric side
- Metric - graduated meters to millimeters; numbered right to left in meters and millimeters
- English side - graduated feet and inches to 1/8ths; numbered right to left



## E1 CHROME CLAD® & YELLOW CLAD

- 1/4" and 3/8" widths
- Chrome Clad® and yellow clad blade
- Markings on one side only
- Graduated to feet, 1/10ths and 1/100ths with a blank space at last end



## E3 CHROME CLAD® & YELLOW CLAD

- 1/4" and 3/8" widths
- Chrome Clad® blade
- Yellow clad available in 1/4" only
- Black markings one side only
- Graduated feet and inches to 1/8ths with instantaneous readings
- 16" centers indicated by a diamond symbol on 3/8" width only



## E5 NY-CLAD® YELLOW

- 1/2" width only
- Nylon-clad yellow blade
- Black and red markings one side only
- Graduated feet to 1/10ths and 1/100ths
- Numbered with feet in red and 1/10ths in black