

Tough gets the job done.  
Smart gets the job done right.

## L600 POWER TAPES

- High visibility case and name tag for easy identification on the jobsite
- Smooth action lock button is easily accessible to the user
- High legibility markings making the blade easy to read
- Integrated nail slot for solo measurements
- Tether slot for working at heights



Cat. No.	Blade Width	Blade Length	Blade Style	Magnetic	Product Weight
L610-02	1/2 in	10 ft	A5	No	0.235 lb
L616-02	3/4 in	16 ft	A5	No	0.470 lb
L625-02	1 in	25 ft	A5	No	0.815 lb
L610CME-02	1/2 in	10 ft	A12	No	0.200 lb
L616CME-02	3/4 in	16 ft	A12	No	0.465 lb
L625CME-02	1 in	25 ft	A12	No	0.855 lb

## L600 SELF CENTERING POWER TAPE

- Self centering blade shows the midpoint of any measurement



Cat. No.	Blade Width	Blade Length	Blade Style	Magnetic	Product Weight
L625SC-02	1 in	25 ft	A23	No	0.890 lb

## QUICKREAD® TAPE MEASURES

- Ergonomic case design for better fit in-hand during measuring
- Overmold case protects the tape from impact and makes it easier to grip
- Toggle lock positioned on top of the tape doesn't require sliding to lock
- Graduations printed in fractions and decimal equivalents, then vertically oriented for quicker measurement reading



Cat. No.	Blade Width	Blade Length	Blade Style	Magnetic	Product Weight
PQR1312N	3/4 in	12 ft	A3	No	0.60 lb
PQR1316N	3/4 in	16 ft	A3	No	0.62 lb
PQR1425N	1 in	25 ft	A3	No	1.07 lb

## PEERLESS

- Designed for engineers and surveyors who prefer a 4-arm reel
- Reel is nickel plated, 4-arm, with rollers in each arm for smooth winding
- Open design construction aids in drying line and clearing out dirt
- Long, easy-action winding handle locks line in any position
- Chrome Clad® and yellow clad blade
- Blade 1/4"/6mm wide and 0.016"/0.4mm thick
- Pair of 580 finger rings and a 579 engineer's conversion rule are furnished with tape or replacement line
- Reel available separately



Cat. No.	Blade Width	Blade Length	Blade Style	Product Weight
C1276N	1/4 in	100 ft	E3	2.40 lb
C1276DN	1/4 in	100 ft	E1	2.40 lb
Y1276DN	1/4 in	100 ft	E1	2.10 lb
C1278N	1/4 in	200 ft	E3	3.70 lb
C1278DN	1/4 in	200 ft	E1	3.70 lb



### A1 YELLOW CLAD

- Black and red markings one side only
- Graduated feet and inches to 1/16ths top edge
- Graduated inches to 1/16ths bottom edge, first 12" to 1/32nds
- Instantaneous foot readings
- Stud marks every 16"




### A2 YELLOW CLAD

- Black and red markings one side only
- Graduated feet and inches to 1/16ths top edge
- Graduated inches to 1/16ths bottom edge, first 12" to 1/32nds
- Instantaneous foot readings
- Stud marks every 16"



### A3 YELLOW CLAD

- Graduated feet and inches to 1/16ths top and bottom edge
- Vertical numbering
- Fractional and decimal equivalent marking
- Stud marks every 16"



### A4 YELLOW CLAD

- Graduated feet, 1/10ths and 1/100ths top edge; feet, inches and 1/16ths on bottom edge
- Instantaneous foot readings
- Stud marks every 16"



### A5 YELLOW CLAD AND BLACK

- Black and red markings one side only
- Consecutive inches to 16ths
- Stud marks every 16", Truss marks every 19.2"
- Instantaneous foot readings



### A6 CHROME CLAD®

- Chrome Clad® blade
- Black markings one side only
- Graduated to 1/10ths of inches on both edges